



TECHNICAL DATA SHEET

Rescue Master 12v Lifeboat Light

Daniamant design and manufacture all of our products in line with the relevant worldwide approvals, technical specifications, current legislation and International directives.

Our mission is to achieve World class performance through partnerships with our suppliers, customers and employees, providing products and services that enhance the safety and security of our customers.

Daniamant products cover 11 key areas:

- Lifejacket Lights
- Liferaft Lights
- Lifebuoy Lights
- Intrinsically Safe Lights
- Special Lights
- LED Flares
- Bridge Navigational Watch Alarm System (BNWAS)
- Salinometers
- Electronic Inclinator
- Forward Looking Sonar
- Agency for a range of world-renowned safety product brands (supplied to the Danish market)

Further Information

For further information on our products, please see our website: www.daniamant.com

MODEL	12V 1A	12V 5W
Part number	23-007-XXXXA	23-016-XXXXXA
Colour	Orange body and lead	Black body orange lead
Mounting Location	External	Internal
Light Output	Minimum 4.3 cd	Minimum 0.5 cd
Light Duration	Minimum 12 hours	Minimum 12 hours
Light Type	Flashing Light	Steady Light
Flash Rate	50-70 flash/min	N/A
Voltage	12 V	12 V
Storage Temperature	-52 °C to 65 °C	-52 °C to 65 °C
Operating Temperature	-52 °C to 65 °C	-52 °C to 65 °C
Storage Life	Requires annual inspection	Requires annual inspection
Activation	External power	External power
Approvals	See website	See website

Transport Specification

Transport Regulations are subject to change. Please contact Daniamant for details.

Spare Parts

Please contact Daniamant for servicing options.

Packing Specification

For units with 1000 mm lead length:

12V1A:

- 50 off in a box 31 x 32 x 32 cm, 6.4 kg.
- 100 off in a box 50 x 40 x 30 cm, 12.8 kg.

12V5W:

- 50 off in a box 31 x 32 x 32 cm, 6.3 kg.
- 100 off in a box 50 x 40 x 30 cm, 12.6 kg.